

QUICK COUPLING VALVES

Quick Coupling Keys

7640

Quick Coupling Key
3/4" male x 1/2" female

7641

Quick Coupling Key
1" male x 3/4" female

Quick Coupling Valves 1"

7642

Quick Coupling Valve with
Yellow Non-Locking Cover
1" NPT (25,4 mm)

7642B

Quick Coupling Valve with
Yellow Non-Locking Cover
1" BSP (25,4 mm)

7643

Quick Coupling Valve with
Yellow Locking Cover
1" NPT (25,4 mm)

7643B

Quick Coupling Valve with
Yellow Locking Cover
1" BSP (25,4 mm)

7644

Quick Coupling Valve with
Lavender Non-Locking Cover
1" NPT (25,4 mm)

7644B

Quick Coupling Valve with
Lavender Non-Locking Cover
1" BSP (25,4 mm)

7645

Quick Coupling Valve with
Lavender Locking Cover
1" NPT (25,4 mm)

7645B

Quick Coupling Valve with
Lavender Locking Cover
1" BSP (25,4 mm)

8649

QCV Locking Cover Key

7640/7641




7645



7643



8810, 8811, 8812



Quick Coupler Keys Swivel [NPT]

8810

3/4" Female NPT x 3/4" Male Hose

8811

1" Female NPT x 3/4" Male Hose

8812

1" Female NPT x 1" Male Hose

FEATURES

Signature[®] quick coupling valves and keys use ACME[®] threads for slow and steady flow control instead of immediate on/off. All models feature rubber cover. Optional locking cover available. Optional lavender rubber cover identifies reclaimed water site – molded in "RECLAIMED WATER - DO NOT DRINK": in English and Spanish. 10 Per Box



ACME[®] threads provide convenient flow control

QUICK COUPLING KEYS

Model	For Valve Models	Thread Size		Height	Thread Size		Height
		MALE	FEMALE		MALE	FEMALE	
7640	All models	3/4"	1/2"	5 1/4"	25,4 mm	19,05 mm	13,3 cm
7641	All models	1"	3/4"	5 1/4"	19,05 mm	12,7 mm	13,3 cm

ENGLISH

METRIC

QUICK COUPLING VALVES

Quick Coupler Model	Rubber Cover	Locking Cover	Warning Cover	Max Capacity GPM	Bottom Pipe Thread	Overall Height	Max Capacity l/m	Bottom Pipe Thread	Overall Height
7642 & B	•			20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7643 & B	•	•		20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7644 & B	•		•	20	1"	3 3/4"	75,7	25,4mm	9,5 cm
7645 & B	•	•	•	20	1"	3 3/4"	75,7	25,4mm	9,5 cm

ENGLISH

METRIC

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

18 Goodyear • Suite 110
Irvine • California • 92618
Tel: 949.580.3640
Fax: 949.580.3645

USA Toll Free: 866.4SIGNATURE

MANUFACTURING FACILITY

8800 N.Allen Rd.,
Peoria • Illinois • 61615
Tel: 949.580.3640
Fax: 949.580.3645

EUROPE & MIDDLE EAST

5 rue de la Vallée Yart
78640 Saint Germain de la Grange
France
Tel: +33.13.489.9056
Fax: +33.13.489.6025

REGIONAL OFFICES

ASIA
NanXian Plaza • MinZhi Street • Shenzhen,
Guangdong Province • 518131
Tel: (86) 136.00419465 • Fax: (86) 755.83275012
SOUTH AMERICA
Av Paseo Los Bravos 6000 • Lo Barnechea
Santiago • Chile
Tel/Fax: +56 229.556220

www.SignatureControlSystems.com

MEXICO, CENTRAL AMERICA
Ribera Escondida 118 • Riberas Del Campestre
38080 Celaya • Gto. • Mexico
Tel/Fax: +52 (461) 614.2322

AFRICA
P.O. Box 1260 • Strubensvalley 1735
Rooodepoort • South Africa
Office & Mobile: +27 82 553 9093 • Fax: 086 670 6318