

BATTERY OPERATED CONTROLLERS

SoloRain[®]

8010

Programmable Actuator

8012

Programmable Actuator with 7901 Valve



SPECIFICATIONS

FEATURES

SoloRain[®] 8010 Series:

- FITS ALL SIGNATURE[®] TURF VALVES
- Compatible with most valves via adapters
- Single program stand-alone unit includes three dials for easy programming
- Waterproof design in both the programmable actuator and the battery compartment - IP68 tested
- Solenoid and battery compartment are compact and made of durable nylon with protective cover included
- Operates on a single 9 volt Energizer[®] alkaline battery for one year depending on usage (not included)
- Latching solenoid design uses minimal battery consumption
- Resistant to the hazards of lightning and power surges commonly seen in AC systems
- Programmable clock for real time operation
- Automatic watering up to two times per day
- Watering times from 1-2 minute to 5½ hours
- Manual ON and OFF

DIMENSIONS (H X W X D)

4½" (11,5 cm) x 2¾" (7 cm) x 1¾" (4,5 cm)

ELECTRICAL:

One 9V Alkaline Battery (not included)



VALVE COMPATIBILITY CHART

8010/8030/8090DC Adapter Kit #77440:

SIGNATURE 9001,9003,9002,9011,9013,9012,
7901,7916,7911,7917,9501,9501FC,
9502,9515NC,9520NC, 9515BC,9520BC,

Adapter Kit #77422:

TORO: 252 (1.5" 2"),220	BERMAD 1"
IRRITROL: 2400,2600,2500,2700, 311,2623,300,700,100, 216,623DPR	DOROT 1"
K-RAIN 7001,7200	GALCON 1"
	GRISWOLD 1"

Adapter Kit #77423:

TORO: EZ FLOW,TPV

Adapter Kit #77424:

RAIN BIRD:
DV,DVF,ASVF,JTV,JTVF,PGA,PEB,PESB,GBR,EFB,BPE,BPES

Used without an adapter kit:

HIT: 100,200,300,500,800,8400

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

16485 Laguna Canyon Rd., Suite 130, • Irvine • California • 92618
Tel: 949.580.3640 • Fax: 949.580.3645

MANUFACTURING FACILITY

8800 N.Allen Rd., • Peoria • Illinois • 61615
Tel: 949.580.3640 • Fax: 949.580.3645

www.SignatureControlSystems.com

EUROPE & MIDDLE EAST

5 rue de la Vallee Yart • 78640 Saint Germain de la Grange • France
Tel: +33.13.489.9056 • Fax: +33.13.489.6025

USA TOLL FREE:

8 6 6 . 4 S I G N A T U R E