

BATTERY OPERATED CONTROLLERS

SoloRain[®]

8014

DuraLife[®] Valve Actuator

8014SR

DuraLife[®] Valve Actuator with Sensor Ready

8013E

DuraLife[®] Valve Actuator with 1" (25,4 mm) 9003 valve

8015 (8015E)

DuraLife[®] Valve Actuator with 1" (25,4 mm) 7901/7916 valve

8016E

DuraLife[®] Valve Actuator with 1" (25,4 mm) 9501 valve



SPECIFICATIONS

DIMENSIONS (H X W X D)

8014, 8014SR: 5½" (14 cm) x 3½" (9 cm)
 8013E: 7¾" (18,8 cm) x 5" (12,7 cm) x 3" (7,6 cm)
 8015, 8015E: 7½" (19 cm) x 4" (10,2 cm) x 3½" (8,9 cm)
 8016E: 8½" (20,6 cm) x 5½" (14 cm) x 3½" (9 cm)

ELECTRICAL:

Factory installed 3.6 V Lithium Battery

VALVE COMPATIBILITY CHART

SoloRain[®] 8014 and 8020 DC ADAPTERS* Model 77467

ALL HARDIE/IRRITROL VALVES
 NELSON TURF:
 7937, 7987, 7938, 7988, 7904, 7914, 7925, 7927,
 7928, 7937, 7938, 7987, 7988,
 TORO: EZ FLOW, TPV
 K-RAIN: 7001, 7200, 7200

Model 77468

RAINBIRD:
 PEB, DV, DVF, ASVF, EFB, GB, PGA, PESB, BPE, BPES

Model 77481

WEATHERMATIC:
 ALL WEATHERMATIC VALVES

Model 77516

HUNTER:
 ALL HUNTER VALVES

Model 77526

TORO:
 252 (1.5" -2"), 220

* Sold separately. No adapter required on the following Signature Valves:
 7901, 7911, 7916, 7917, 9001, 9002, 9003, 9011, 9012, 9013, 9501,
 9501FC, 9502, 9515BC, 9515NC, 9520BC, 9520NC.
 This is a partial list; please contact Signature for further details.

* Battery life will vary depending on environmental conditions.
 Test results have shown 2 - 3 years of battery life

FEATURES

SoloRain[®]

8014 Series:

- FITS ALL SIGNATURE[®] TURF VALVES
- Long life factory installed lithium battery*. Actual battery life will depend on the number of cycles run per year, valve size, operating pressure, and temperature. The battery is replaceable and is available as a service part.
- LCD displays clock and programming
- Timed manual ON and OFF
- Length of watering time: 1 minute to 12 hours
- Six watering programs available per day
- Mist Cycle available on all 6 programs
- Days of the week, Odd/Even, and Interval scheduling
- Rain Delay is programmable from 1 to 99 days
- Leap year compatible-automatically includes Feb. 29th every four years
- Waterproof design tested to IP68, 6 ft (1,8m)

8014SR

- Two wires on the "SR" version allows any normally open/normally closed sensor to be hooked up to it (switch has to be closed for the 8014 to operate). Sensors can be up to 25 ft (7,5 m) away.

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

16485 Laguna Canyon Rd., Suite 130 • Irvine • California • 92618
 Tel: 949.580.3640 • Fax: 949.580.3645

MANUFACTURING FACILITY

8800 N. Allen Rd., • Peoria • Illinois • 61615
 Tel: 949.580.3640 • Fax: 949.580.3645

www.SignatureControlSystems.com

EUROPE & MIDDLE EAST

5 rue de la Vallée Yart • 78640 Saint Germain de la Grange • France
 Tel: +33.13.489.9056 • Fax: +33.13.489.6025

USA TOLL FREE:

866.4SIGNATURE