

BATTERY OPERATED CONTROLLERS

SPECIFICATIONS

SoloRain[®]

8030

Remote Programmable Actuator

8032 (8033)

Remote Programmable Actuator with 1" (25,4 mm) 7901/7916 valve

8071

Programmer Plus console

Note: Versions in parenthesis feature BSP threading for international use



8071

8030

8032



FEATURES

SoloRain[®] 8030 Series:

- FITS ALL SIGNATURE[®] TURF VALVES
- Compatible with most valves via adapters
- Solenoid and 9V battery compartment are compact and made of durable nylon construction
- Programming interface through cord connection to the model 8071 Programmer control console
- Waterproof design tested to IP68, 6 ft (1,8m). [Note: Removal of Programmer Socket Protection Cap wet environments, voids the waterproofing claim and potential for warranty]
- Latching solenoid design uses minimal battery consumption

SoloRain[®] 8071:

- Independent programming of an unlimited number of 8030 series actuators
- Up to 16 irrigation start times per actuator
- 14-day programming calendar
- Built-in memory allows storage of up to 36 different irrigation programs
- Downloadable transfer of programs individually or to a group of actuators
- Memory is retained for 2 minutes during battery change
- Four line LCD display for easy menu guided programming
- User can choose between five languages for operation

DIMENSIONS (H X W X D)

8030: 4½" (11,5 cm) x 2¾" (7 cm) x 1¾" (4,5 cm)

8032: 7" (17,8 cm) x 4¾" (12 cm) x 2¾" (7 cm)

8071: 97/8" (25,1 cm) x 5¼" (13,3 cm) x 1¼" (3,2 cm)

ELECTRICAL:

One 9V Alkaline Battery (not included)

VALVE COMPATIBILITY CHART

8010/8030/8090DC (¾" – 20 Threads 9VDC) Adapter Kit #77440:

SIGNATURE 9001,9003,9002,9011,9013,9012,
7901,7916,7911,7917,9501,9501FC,
9502,9515NC,9520NC,9515BC,9520BC,

Adapter Kit #77422:

TORO:	BERMAD
252 (1.5" 2"),220	1"
IRRITROL:	DOROT
2400,2600,2500,2700,	1"
311,2623,300,700,100,	GALCON
216,623DPR	1"
K-RAIN	GRISWOLD
7001,7200	1"

Adapter Kit #77423:

TORO: EZ FLOW,TPV

Adapter Kit #77424:

RAIN BIRD:
DV,DVF,ASVF,JTV,JTVF,PGA,PEB,PESB,GBR,EFB,BPE,BPES

Used without an adapter kit:

HIT: 100,200,300,500,800,8400

- Easy to program with large LCD display and simplified four rubber button keypad with audio "beep" response
- Impact-resistant plastic housing
- Operates on one 9 volt alkaline battery
- Programmable 12 or 24-hour clock with synchronizing function
- Watering times from one minute to 24 hours in one minute increments
- Manual START and STOP function
- Program review
- Rain ON/OFF capability

SIGNATURE CONTROL SYSTEMS, INC.

WORLD HEADQUARTERS

16485 Laguna Canyon Rd., Suite 130, • Irvine • California • 92618
Tel: 949.580.3640 • Fax: 949.580.3645

MANUFACTURING FACILITY

8800 N.Allen Rd., • Peoria • Illinois • 61615
Tel: 949.580.3640 • Fax: 949.580.3645

www.SignatureControlSystems.com

EUROPE & MIDDLE EAST

5 rue de la Vallée Yart • 78640 Saint Germain de la Grange • France
Tel: +33.13.489.9056 • Fax: +33.13.489.6025

USA TOLL FREE:

866.4SIGNATURE