

SHARE™ 8250

Residential

Indoor, 4 to 12 Station, Integrated Ethernet Port, Web-Based Intelligent Irrigation Controller

FEATURES

- Model Type: Indoor
- Enclosure Type: Plastic, Wall Mount
- Programming Type: Basic or Intelligent
- Number of Stations: 4, 6, 8, 10, 12
- Number of Programs: 16
- Programmable Events: 64
- Number of Start Times: 4
- Master Valve Pump Starts: 1
- Run Times: 1 Min to 17 Hrs 59 Min
- Integrated Sensor Terminals: 1
- Flexible Scheduling Options:
 - Day(s) of Week
 - Day(s) of Month
 - Day(s) of Year
 - Day(s) to Skip (1-99 Days)
 - Odd/Even
- Qualifies for Water Conservation Rebates
 - EPA WaterSense Approved (Intelligent models only)

COMMUNICATION

- Integrated Ethernet Port: 10MB, RJ-45 Connector



POWERLINE ADAPTER
(Ethernet Over Power)



WI-FI BRIDGE



HOW TO ORDER

8250 -12-12-USA				
Model	Stations	Program Type	Communication Type	Country Code
8250	04	B = Basic	2 = Integrated Ethernet	USA = United States
	06	I = Intelligent	8 = Powerline Adapter	ISO*
	08		9 = Wi-Fi Bridge	
	10			
	12			

*International models - Enter ISO country code ie. Spain = ESP, France = FRA, etc.

ELECTRICAL SPECIFICATIONS

Power Input

USA & Canada: 120VAC, 60Hz
International: 230VAC, 50Hz

Station Output

All Models: 24VAC, 0.83 Amp

Max Load Per Station

All Models: 0.83 Amp

Station Capacity

All Models: One 24VAC, 6VA Solenoid Valve per Station Plus a Master Valve

DIMENSIONS (H X W X D)

Cabinet:

7" (17,8 cm) x 5 5/8" (14,3 cm) x 2" (5,1 cm)

Enclosure Material: Plastic

Enclosure Type: Indoor

CERTIFICATIONS

Industry/Testing: UL, cUL, CE, CSA, C-tick, FCC Part 15

