

SHARE™ 8260

Residential

Indoor, 4 to 12 Station, Choice of Integrated Cellular or Wi-Fi Modem, Web-Based Intelligent Irrigation Controller

FEATURES

- Model Type: Indoor
- Enclosure Type: Plastic, Wall Mount
- Programming Type: Basic or Intelligent
- Number of Stations: 4, 6, 8, 10, 12
- Number of Programs: 16
- Programmable Events: 64
- Number of Start Times: 4
- Master Valve Pump Starts: 1
- Run Times: 1 Min to 17 Hrs 59 Min
- Integrated Sensor Terminals: 1
- Flexible Scheduling Options:
 - Day(s) of Week
 - Day(s) of Month
 - Day(s) of Year
 - Day(s) to Skip (1-99 Days)
 - Odd/Even
- Qualifies for Water Conservation Rebates
 - EPA WaterSense Approved (Intelligent models only)

COMMUNICATION

- Integrated Cellular Modem
 - GSM Radio
 - CDMA Radio
- Integrated Wi-Fi Modem
- Optional Remote Communication with RF (iWAN)

HOW TO ORDER

8260 -12-14-USA				
Model	Stations	Program Type	Communication Type	Country Code
8260	04	B = Basic	4 = GSM Radio Only	USA = United States
	06	I = Intelligent	5 = CDMA Radio Only	ISO*
	08		6 = GSM Radio + RF (iWAN)	
	10		7 = CDMA + RF (iWAN)	
	12		10 = Wi-Fi Modem Only	
			12 = Wi-Fi + RF (iWAN)	

*International models - Enter ISO country code ie. Spain = ESP, France = FRA, etc.



ELECTRICAL SPECIFICATIONS

Power Input

USA & Canada: 120VAC, 60Hz

International: 230VAC, 50Hz

Station Output

All Models: 24VAC, 0.83 Amp

Max Load Per Station

All Models: 0.83 Amp

Station Capacity

All Models: One 24VAC, 6VA Solenoid Valve per Station Plus a Master Valve

DIMENSIONS (H X W X D)

Cabinet:

7" (17,8 cm) x 5 5/8" (14,3 cm) x 2" (5,1 cm)

Enclosure Material: Plastic

Enclosure Type: Indoor

CERTIFICATIONS

Industry/Testing: UL, cUL, CE, CSA, C-tick, FCC Part 15

